

## SCBA

### SELF CONTAINED BREATHING APPARATUS



- High performance breathing apparatus
- Positive pressure full face mask
- Offers maximum respiratory protection
- Flame retardant, waterproof and antistatic back frame and harness
- With manometer & whistle (>90Db sound) warning the user when the air pressure is dropping down below 50 bar



**SOLAS / MED APPROVED**

*Packed in a heavy-duty plastic carrying case*



**The SCBA is available in two versions, with 6L & 9L cylinders. Both versions contain the following parts:**


- Breathing apparatus carrier with harness
- Pressure regulator with manometer & whistle
- Pressure & air flow regulator
- Breathing Apparatus face mask
- Compressed air cylinder with an EU standard cylinder valve with G5/8" thread

The SCBA is also available without cylinder.

Code	Cylinder Volume (L)	Cylinder Material	Working Pressure (Bar)	Warning Pressure (Bar)	Weight (kg)	Carrying Suitcase Dimensions (cm)
71327	6	Steel	300	50-60	≤15	270x490x755
713271	Will accept wide range of 300 bar cylinders. The air cylinders shall be designed in accordance with national regulations, bearing an EU standard cylinder valve with G5/8" thread. Please refer to user instructions for further information.				N/A	270x490x755
71328	9	Carbon Composite	300	50-60	≤12	280x445x735

Portable radio sets (ATEX or IECEX ) can be supplied with the SCBA upon request.

**Spare Compressed Air Cylinder 6lt & Valve 300bar**



Code: 02302

**Spare Compressed Air Cylinder 9lt & Valve 300bar**



Code: 02303

The product is MED/SOLAS certified under the requirements of Marine Equipment Directive 2014/90/EU as amended and tested per Standards: • SOLAS 74 as amended • Regulation II-2/10 & X/3 • 2000 HSC Code 7 • FSS Code 3 • IBC Code 11 • IGC Code 11 and IMO MSC.1/Circ.1499 • IMO MSC.1/Circ.1555 • EN 137:2006 • EN 136:1998 including AC: 1999 and AC: 2003, ISO 23269-2:2011



**Product Video**