

PRODUCT DATA SHEET

EEBD

EMERGENCY EVACUATION BREATHING DEVICE





ESCAPE-15

Code: 70321

- Full-face hood universal size, suitable for every face shape
- Durable, elastic and non-irritant neoprene neck seal
- 15 min. steady air-flow with sufficient air-delivery rate
- EU standard valve with G 5/8" charging thread
- Flame resistance
- Activated with a single move



- Easy visual access on the pressure gauge
- Durable & reliable construction with low maintenance
- Silver colour to reflect heat and be highly visible
- Easy to refill cylinder (no adaptor required)



SOLAS / MED APPROVED

Technical Specifications

The Tel	
Working temp. range	-10°C to 65°C
Length (cm)	50
Height (cm)	22
Width (cm)	13
Weight (grams)	6.150
Volume (cm³)	14.300

our network.

- Tested according to ISO 23269-1:2008 and EN 1146:2005



Product Video

^{*} The product is MED/SOLAS certified under the requirements of Marine Equipment Directive 2014/90/EU as amended and tested per Standards: • SOLAS 74 as amended • Regulation II-2/13 • FSS Code 3 • IMO MSC/Circ. 849



Global Service & Supply Network



- ✓ Global service network through owned locations & third-party service providers
- ✓ Global supply of LSA, FFE and spare parts
- Certified quality standards by major classification societies
- ✓ Robust warranty supported directly by the manufacturer
- ✓ Streamlined after-sales support via our ticketing system

Safety is not just a product, it is an ongoing process!